

Tax I the f

# **QUALITY INSTALLATION KIT**

CH







www.cooperandhunter.us

### **MAX Series**

Model	Line Set Size	Copper Line Length 4/16 AWG Cable		Rubber Drain Hose
PJX-N1-C16MAX	1/4" - 3/8"	16ft	18ft	16ft
PJX-N1-C25MAX	1/4" - 3/8"	25ft 29.5ft		16ft
PJX-N1-C50MAX	1/4" - 3/8"	50ft	55.8ft	16ft
PJX-N2-C16MAX	1/4" - 1/2"	16ft	18ft	16ft
PJX-N2-C25MAX	1/4" - 1/2"	25ft	29.5ft	16ft
PJX-N2-C50MAX	1/4" - 1/2"	50ft	55.8ft	16ft
PJX-N3-C16MAX	3/8" - 5/8"	16ft	18ft	16ft
PJX-N3-C25MAX	3/8" - 5/8"	25ft	29.5ft	16ft
PJX-N3-C50MAX	3/8" - 5/8"	50ft	55.8ft	16ft
PJX-N4-C50MAX	3/8''- 3/4''	50ft	55.8ft	16ft

## 0

Compatibility table:		n			The second state and the second state of the s	
Line Sets		Wall Mount	Duct	Ceiling Cassette	Floor Console	Universal Floor Ceiling
РЈХ-N1-С16МАХ РЈХ-N1-С25МАХ РЈХ-N1-С50МАХ	1/4" - 3/8"	9,000 BTU/h - 230V	9,000 BTU/h	9,000 BTU/h		
РЈХ-N2-С16МАХ РЈХ-N2-С25МАХ РЈХ-N2-С50МАХ	1/4" – 1/2"	9,000 BTU/h - 115V 12,000 BTU/h 18,000 BTU/h	12,000 BTU/h 18,000 BTU/h	12,000 BTU/h 18,000 BTU/h	12,000 BTU/h	18,000 BTU/h
РЈХ-N3-С16МАХ РЈХ-N3-С25МАХ РЈХ-N3-С50МАХ	3/8" - 5/8"	24,000 BTU/h 30,000 BTU/h 36,000 BTU/h	24,000 BTU/h 36,000 BTU/h 48,000 BTU/h	24,000 BTU/h 36,000 BTU/h 48,000 BTU/h		24,000 BTU/h 36,000 BTU/h 48,000 BTU/h
PJX-N4-C50MAX	3/8" - 3/4"		60,000 BTU/h			60,000 BTU/h



#### LINE SETS:

99.9% Copper (ASTM B-280) Pre-insulated (ASTM D154) UV & UV-C Protected Pre-flared

## ALSO INCLUDES:

4/16 AWG connecting cable Rubber draine hose Bandage tape Wall sleeve Neoprene

#### **COMPARE DRAIN HOSES**

1 -

-



Generic plastic hose



Cooper&Hunter rubber hose with plastic coil

Your actual Multi-Room Inverter Heat Pump system and related devices may differ from images shown in this specification sheet. Test conditions are based on AHRI 210/240. Specifications are subject to change whithout notice. Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without incurring obligations. © 12.2020 All rights reserved.

Scan to learn more about **C&H Installation Kits** 

