

**Job Name:** \_\_\_\_\_  
**Location:** \_\_\_\_\_  
**Engineer:** \_\_\_\_\_  
**Submitted to:** \_\_\_\_\_  
**Submitted by:** \_\_\_\_\_  
**Reference:** \_\_\_\_\_

**Date:** \_\_\_\_\_  
**Approval:** \_\_\_\_\_  
**Construction:** \_\_\_\_\_  
**Unit #:** \_\_\_\_\_  
**Drawing #:** \_\_\_\_\_



### KEY FEATURES:

- LED display
- Smart Kit Ready
- Quiet operation
- Multiple fan speeds (LOW/MED/HI/TURBO)
- Auto-swing for vertical louvers




### SPECIFICATIONS:

Indoor Model			CH-B12MOLVWM-230VI
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	12,000
Heating	Rated Capacity	Btu/h	12,000
Minimum Circuit Ampacity (MCA)		A	3
Max. Fuse		A	15
Indoor Air Flow (Hi/Mi/Lo)		CFM	341.18/291.18/194.12/152.94
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	41.5/36/24
External static pressure (SlimDuct/AHU only)		in. WG	
Drainage water pipe diameter		inch	5/8"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	1/4" / 1/2"
Dehumidification		Pnt/H	3.06
Communication wiring			16AWG*4
Indoor	Dimension (WxDxH)	inch	31.57x7.85x11.61
	Packing (WxDxH)	inch	34.45x11.22x14.96
	Net/Gross Weight	lbs.	18.74/24.25

# OLIVIA

Units: in



**Dimension (WxDxH)**  
**31.57x7.87x11.61**