

Job Name: _____
Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Date: _____
Approval: _____
Construction: _____
Unit #: _____
Drawing #: _____



KEY FEATURES:


- Up to 5 Zone
- Inverter Technology
- HIGH-FREQUENCY RACER TECHNOLOGY: Enables the compressor to reach maximum speed within 6 seconds on start up.
- HIGH-EFFICIENCY PIPES: 54 teeth to increase heat exchange.
- INTELLIGENT DUSTING SWITCH: Reverses the fan to clean dust, sand, and other debris from the coil.
- The Cooper&Hunter standard warranty offers seven years on the compressor and five years on parts.

Cooling Capacity		Heating Capacity	SEER2	EER2	COP
Btu/h	Btu/h	Btu/h			
55,000(19,400~57,000)	55,000(15,500~61,500)		18.8	10.5	3.1

**Please note: for ducted solutions, values are represented with Outdoor Units combined with Indoor ducted units. Values will vary with depending on the combination of Outdoor/Indoor models used.*

SPECIFICATIONS:

Outdoor Model			CH-HPR55M-230VO	
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz	
Cooling	Rated Capacity (range)		Btu/h	
	Rated Capacity (range)		55,000(19,400~57,000)	
Heating	HSPF4		9.3	
	HSPF5		7.3	
Minimum Circuit Ampacity (MCA)		A	40	
Max. Fuse		A	60	
Rated current (RLA)		A	23.5(3.7~27.2)	
Compressor	Model		EAPQ420D1UMUA	
	Type		ROTARY	
	Brand		GMCC	
	RLA		A	25
	Input		w	3,565
	Refrigerant oil		oz	VG74 49.4
Outdoor fan motor	Qty		2	
	Input		w	126
	RLA		A	2.5
Outdoor air flow (Max)		CFM	4,500	
Outdoor noise level (Max)		dB(A)	61	
Outdoor unit	Dimensions (WxDxH)		in	37.48x16.34x52.48
	Packing (WxDxH)		in	43.11x19.49x58.27
	Net/Gross weight		in	233.03/265.87
Refrigerant	Type/Quantity		oz	R410A
	Precharge		ft	25x5
	Additional Charge (liquid pipe)		oz	162.26
Design pressure		PSIG	550/340	
Refrigerant piping	Liquid side/Gas side		in	5x1/4" 3x3/8"+2x1/2"
	Max. length for all indoor units		ft	262.46
	Max. length for one indoor unit		ft	114.83
	Max. height difference between indoor and outdoor		ft	49.21
	Max. height difference between indoor units		ft	33
Ambient temperature	Cooling		F	5~122
	Heating		F	-22~75



Unit	W	D	H	W1	A	B
mm	952	415	1333	1060	634	404
inch	37.5	16.3	52.5	41.7	25.0	15.9