

Job Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Engineer: \_\_\_\_\_  
Submitted to: \_\_\_\_\_  
Submitted by: \_\_\_\_\_  
Reference: \_\_\_\_\_

Date: \_\_\_\_\_  
Approval: \_\_\_\_\_  
Construction: \_\_\_\_\_  
Unit #: \_\_\_\_\_  
Drawing #: \_\_\_\_\_



### OUTDOOR UNIT FEATURES:

- ◆ Reliable and stable stepless inverter-driven technology.
- ◆ Anti-frost design includes an expanded heat exchanger, which provides a larger surface area for higher heat exchanging efficiency and smooth condensate drainage.
- ◆ 360°F refrigerant cooling technology safely and efficiently dissipates heat from the main PCB, inverter module, and outdoor unit electrical box.
- ◆ Intelligent defrosting mode utilizes 3 sensors to determine the optimal time to melt and remove frost from the outdoor unit.
- ◆ Static pressure of the outdoor unit up to 0.44 in.w.g.
- ◆ Heating operations to -22°F.
- ◆ Nominal Capacity on heating till -4°F.



Model name			CHV6-072SRBHH	
Nominal tonnage		RT	6	
Cooling capacity	Nominal capacity	Btu/h	72,000	
	Input power (Ducted/Non-ducted)	kW	6.00	
	EER (Ducted/Non-ducted)	Btu/h	12.0 / 12.8	
	IEER (Ducted/Non-ducted)	Btu/h	19.5 / 23.0	
Heating capacity	Nominal capacity	Btu/h	81,000	
	Input power (Ducted/Non-ducted)	kW	6.49	
	COP 47°F (Ducted/Non-ducted)	W/W	3.65 / 4.25	
Power supply		V, Ph, Hz	460V, 3Ph, 60Hz	
Max/Min power supply		V	253 / 188	
Electrical parameters	MCA	A	31.7	
	MOP	A	45	
Min/Max number of connectable indoor units		#	1 / 21	
Total indoor unit capacity		%	50~150% to outdoor capacity	
Dimensions (H x W x D)		in	68 1/8 x 53 5/32 x 29 17/32	
Connection pipe diameter	Heat recovery operation system	Low pressure gas pipe	in	3/4"
		High/Low pressure gas pipe	in	5/8"
		Liquid pipe	in	3/8"
	Heat pump operation system	Low pressure gas pipe	in	3/4"
		Liquid pipe	in	3/8"
Refrigerant			R410A	
Compressor			Scroll Comp	
Compressor quantity			2	
Refrigerant charge before shipment		lbs	17.2	
Weight	Net weight	lbs	816	
	Gross weight	lbs	895	
Total piping length		ft	3,280	
Height difference	Maximum below unit	ft	164 (295* see note)	
	Maximum above unit	ft	131 (295* see note)	
	Between IDUs	ft	49 (98* see note)	
Fan motor	Quantity	#	2	
	Air flow rate	CFM	9,430	

\* Note: maximum height difference can be expanded with assistance from C&H technical support team.

Sound pressure level		dB(A)	58
Operation range	Cooling	°F DB	23~ 126
	Heating	°F DB	-22 ~ 62

**NOTES:**

1. The above specifications demonstrate cooling and heating conditions when the outdoor unit is operated with the 100% rating of indoor units, Cooling operation conditions: indoor air inlet temperature: 80°F DB 67°F WB, Outdoor air inlet temperature: 95°F DB, Piping length: 25ft., Piping lift: 0ft.  
Heating operation conditions: Nominal heating condition, indoor air inlet temperature: 70°F DB, outdoor air inlet temperature: 47°F DB 43°F WB.
2. Rated capacity and efficiency are certified under AHRI Standard 1230. Ratings are subject to change without notice. Current certified ratings are available at [www.ahridirectory.org](http://www.ahridirectory.org).
3. The above noise values were measured in an anechoic chamber without reflected echo. Measurement point: 3.3ft from the service cover surface and 4.9ft from floor level.
4. The final appearance of outdoor units may vary from images shown here.

Unit: inch (mm)

